

# CDVI Readers

## Proximity, keypad, combined

### Wiegand

#### NANO

Mini proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- NANOPB - black
- NANOPW - white
- 70 x 43 x 23mm

#### MOONAR

Flush proximity reader



- Multicolour LED
- Audible feedback
- Fits UK back box
- Operating temp. -30°C to 60°C
- Power 12Vdc
- MOONARWB - black & white covers
- 92 x 85 x 13mm

#### STAR

Mullion proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- STARPB - black
- STARPW - white
- 130 x 41 x 28mm

#### DGLIWLC & DGLIFWLC

Stainless steel proximity readers

DGLIFWLC



DGLIWLC



- Stainless steel proximity reader
- Vandal resistant housing
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 140 x 35 x 22mm DGLIFWLC
- 97 x 76 x 20mm DGLIWLC

#### SOLAR

Standard proximity reader



- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- SOLARPB - black
- SOLARPW - white
- 130 x 90 x 35mm

#### KCPROXWLC

Proximity card reader and keypad



- Vandal resistant housing
- Backlit keys
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 190 x 43 x 27mm

#### SOLARK

Proximity card reader and keypad



- Touch sensitive keypad
- Multicolour LED
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- SOLARKPB - black
- SOLARKPW - white
- 130 x 90 x 35mm

#### GALEO/W

26-bit Wiegand keypad



- Heavy-duty ZAMAK cast alloy
- Soft blue back-lighting
- Audible feedback
- Operating temp. -30°C to 60°C
- Power 12Vdc
- 110 x 75 x 15mm